

CLAIMS

- [001] A drying basket (4) for a drier, with a longitudinal support (14, 15) and a grid-shaped basket 16 secured to it, characterised in that a connecting device (8) is formed integrally on the longitudinal support (14, 15), which device can be engaged with an opening (5, 6) provided on the drier.
- [002] The drying basket according to Claim 1, characterised in that the longitudinal support (14, 15) is designed as a wire, and in that the connecting device (18) is a hook (19, 20), wherein the hook (19, 20) is formed on an end section of the wire, preferably by a bending process.
- [003] The drying basket according to Claim 2, characterised in that the connecting device (18) has, on the longitudinal support (14, 15), a support section (22) with which connecting device (18) is supported on the housing section of the drier.
- [004] The drying basket according to Claim 2 or 3, characterised in that a longitudinal support (14, 15) is arranged on both sides of the drying basket (4), which support can be engaged with an opening (5, 6) provided on the drier by means of connecting devices (18) designed as hooks (19, 20).
- [005] A fastening device for a drying basket (4) on a drier with a housing (26), characterised in that an opening (5, 6) is provided on one section of the housing (26) of the drier, with which opening a connecting device (18) of a drying basket (4) can be engaged.
- [006] The fastening device according to Claim 5, characterised in that the housing (26) has a front end plate (2), and in that the opening (5, 6) is arranged in the front end plate (2).
- [007] The fastening device according to Claim 5 or 6, characterised in that a replaceable lint filter (13) is provided in the housing (26), and in that the opening (5, 6) is arranged adjacent to the lint filter (13).

[008] The fastening device according to any one of Claims 5 to 7, characterised in that the opening (5, 6) is covered by the inserted lint screen (13) both when the drying basket (4) is fitted and when the drying basket (4) is not fitted.

[009] The fastening device according to any one of Claims 5 to 8, characterised in that the lint filter (13) is arranged in the lower section of the front end plate (2), and in that an opening (5, 6) is arranged on each side of the lint filter(13).